US009636032B2

US 9,636,032 B2

(12) **United States Patent**
Thakur et al.

(10) **Patent No.:** US 9,636,032 B2
(45) **Date of Patent:** May 2, 2017

(54) **PERSISTENT DISPLAY OF NEAREST BEAT CHARACTERISTICS DURING REAL-TIME OR PLAY-BACK ELECTROPHYSIOLOGY DATA VISUALIZATION**

(71) Applicant: **Boston Scientific Scimed Inc.**, Maple Grove, MN (US)

(72) Inventors: **Pramodsingh H. Thakur**, White Bear Lake, MN (US); **Shantha Arcot-Krishnamurthy**, Vadnais Heights, MN (US); **Allan C. Shuros**, St. Paul, MN (US); **Sunipa Saha**, Shoreview, MN (US); **Shibaji Shome**, Arden Hills, MN (US); **Barun Maskara**, Blaine, MN (US)

(73) Assignee: **Boston Scientific Scimed Inc.**, Maple Grove, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/270,867**

(22) Filed: **May 6, 2014**

(65) **Prior Publication Data**

US 2014/0330150 A1   Nov. 6, 2014

Related U.S. Application Data

(60) Provisional application No. 61/820,142, filed on May 6, 2013.

(51) **Int. Cl.**
  A61B 5/044   (2006.01)
  A61B 5/042   (2006.01)
  A61B 5/00   (2006.01)

(52) **U.S. Cl.**
  CPC *A61B 5/044* (2013.01); *A61B 5/0422* (2013.01); *A61B 5/6858* (2013.01)

(58) **Field of Classification Search**
  CPC A61B 5/00; A61B 5/04; A61B 5/04011; A61B 5/044; A61B 5/6858
  (Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,649,924 A   3/1987   Taccardi
4,674,518 A   6/1987   Salo
  (Continued)

FOREIGN PATENT DOCUMENTS

CN   1253761 A   5/2000
CN   102917638 A   2/2013
  (Continued)

OTHER PUBLICATIONS

He, Ye H., "An interactive graphical system for automated mapping and display of cardiac rhythms", Journal of Electrocardiology, vol. 32, No. 3, Jul. 1, 1999, pp. 225-241.
  (Continued)

Primary Examiner — Allen Porter, Jr.
(74) *Attorney, Agent, or Firm* — Faegre Baker Daniels LLP

(57) **ABSTRACT**

A system and method for mapping an anatomical structure includes sensing activation signals of intrinsic physiological activity with a plurality of electrodes disposed in or near the anatomical structure. A most recent intrinsic event at a selected time is determined based on the sensed activation signals and a persistent display of relevant characteristics is generated based on the sensed activation signals of the most recent intrinsic event. The persistent display is updated upon detection of a subsequent intrinsic event.

11 Claims, 5 Drawing Sheets